

AMENDMENTS TO THE CLAIMS

1. (Currently amended) An air duct system for a combined refrigerator of the forced air circulation type, comprising:

a freezing compartment (1) and a refrigerating compartment (2), which are superposed and separated by an intermediate wall (3), further ~~having~~ comprising an air cooling compartment (4) lodging an evaporator (5) and a fan (6) and presenting at least one circulated air inlet (4a) and at least one refrigerated air outlet (4b) directed to the freezing compartment (1) and to the refrigerating compartment (2), ~~characterized in that it comprises~~ wherein a body (10) is mounted into the interior of the intermediate wall (3) and ~~defining~~ defines a rear chamber (11) opened to the circulated air inlet (4a);

a transversal through-duct (12) centrally provided in front of the rear chamber (11) and having an end maintained in fluid communication with the refrigerated air outlet (4b), and an opposite end opened to the inside of the refrigerating compartment (2); and

at least one first and one second return duct (13, 14) each presenting a rear end (13b, 14b) opened to the rear chamber (11) and a front end (13a, 14a) opened to the interior of the freezing compartment (1) and of the refrigerating compartment (2), respectively, the rear ends (13b, 14b) of the first and the second return ducts (13, 14) being positioned on opposite sides of the transversal through-duct (12).

2. (Currently amended) The air duct system according to claim 1, ~~characterized in that it comprises~~ comprising:

a pair of first return ducts (13) disposed along respective opposite lateral regions of the body (10) and having a the rear end (13b) opened to the rear chamber (11) and a the front end (13a) opened to the inside of one of the freezing compartment (1) and the refrigerating compartment (2); and

a second return duct (14) centrally disposed between the pair of first return ducts (13) and having a the front end (14a) opened to the inside of the other of said freezing compartment (1) and refrigerating compartment (2), and a the rear end (14b) bifurcated around the transversal through-duct (12) and opened to the rear chamber (11) between the rear ends (13b) of the pair of first return ducts (13).

3. (Currently amended) The air duct system according to claim 2, ~~characterized in that~~ wherein the front ends (13a) of the first return ducts (13) are opened to one of the front lower region of the freezing compartment (1) and the front upper region of the refrigerating compartment (2), the front end (14a) of the second return duct (14) being opened to the other of said regions.

4. (Currently amended) The air duct system according to claim 2, ~~characterized in that~~ wherein the front ends (13a) of the first return ducts (13) are opened to a face of the body (10) turned to one of the freezing compartment (1) and the refrigerating compartment (2) with which the first return ducts (13) are maintained in fluid communication.

5. (Currently amended) The air duct system according to claim 2, ~~characterized in that~~ wherein the rear chamber (11) presents a width corresponding to the width of the circulated air inlet (14a) in the air cooling compartment (4).

6. (Currently amended) The air duct system according to claim 5, ~~characterized in that~~ wherein the rear chamber (11) presents a width substantially equal to the width of the body (10).

7. (Currently amended) The air duct system according to claim 5, ~~characterized in that~~ wherein the width of the circulated air inlet (4a) is substantially equal to the width of the evaporator (5).

8. (Currently amended) The air duct system according to claim 1, ~~characterized in that~~ wherein the first return ducts (13) and the second return duct (14) are substantially coplanar and parallel to each other.

